NETUM NT-8360 Thermal Receipt Printer Specifications

PRODUCT OVERVIEW

Model	NT-8360
Product Type	Thermal Receipt Printer

Print Performance

Printing Method	Direct line thermal
Resolution	203 dpi (8 dots/mm)
Print Speed	220 mm/s
Cutting Method	Partial-cut auto-cutter

Connectivity & Software

Interfaces	USB / LAN / Bluetooth (optional)
Compatibility	Windows 2003 / XP / 7 / 8 / 10 / Linux; iOS / Android supported
Command Languages	ESC/POS

Barcodes & Memory

1D Barcodes	UPC-A, UPC-E, JAN13 (EAN13), JAN8 (EAN8), CODE39, ITF, CODABAR, CODE93, CODE128
2D Barcodes	QR Code, PDF417
Memory	Input buffer: 2048 Kbytes; NV flash: 256 Kbytes
Fonts	Font A: 1.5×3.0 mm (12×24 dots); Font B: 1.1×2.1 mm (9×17 dots); simplified/traditional Chinese: 3.0×3.0 mm (24×24 dots). Character tables: PC437, Katakana, PC850, PC860, PC863, PC865, West Europe, Greek, Hebrew, East Europe, Iran, WPC1252, PC866, PC852, PC858, Iran II, Latvian, Arabic, Thai, PT151 (1251).

Power & Physical Specifications

Power Supply	Input: AC 110 V / 220 V, 50-60 Hz; output: DC 24 V / 2.5 A

Environment & Reliability

Reliability	Printhead: 100 km; cutter: 1.5 million cuts

Other Specifications

Additional Details	Downloadable logo printing; line spacing 3.75 mm, command-adjustable.