NETUM POS-9220 Thermal Label Printer Specifications

PRODUCT OVERVIEW

Model	POS-9220
Product Type	Thermal Label Printer

Print Performance

Printing Method	Thermal printing
Resolution	203 dpi (8 dots/mm)
Print Speed	150 mm/s; customizable 200 mm/s
Effective Print Width	108 mm

Media

Paper / Media Width	20-110 mm
Media Types	Continuous, gap and black mark media
Paper / Media Thickness	0.06-0.254 mm

Connectivity & Software

Interfaces	USB; Bluetooth
Compatibility	Windows / Linux / iOS / Android
Command Languages	TSPL

Barcodes & Memory

1D Barcodes	UPC-A, UPC-E, JAN13 (EAN13), JAN8 (EAN8), CODE39, ITF, CODABAR, CODE93, CODE128
2D Barcodes	PDF417, MaxiCode, Data Matrix, QR Code
Memory	4 MB flash memory
Fonts	GB18030-2000 / BIG5; 24×24 / 16×16; customized font or codepage

Power & Physical Specifications

Power Supply	Input: AC 100-220 V, 50-60 Hz; output: DC 24 V / 2 A
Dimensions	199 × 80 × 91 mm (L × W × H)
Weight	700 g

Environment & Reliability	
Operating Temperature	-5-40 °C
Operating Humidity	20-80% RH, non-condensing
Storage Temperature	-20-60 °C
Storage Humidity	10-90% RH, non-condensing